

Auto 4 Ltd. Unit 4a, Park Court, Park Lane Business Park, Kirkby-in-Ashfield, Nottinghamshire. NG17 9GU General Tel: 01623 727360 Fax: 01623 721950 Email: sales@auto4.co.uk Web: www.auto4.co.uk

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Name: Tyre Bead Lubricant 5 Litre

Product Number: 201110 Updated: June 2016

## 1.2. Relevant identified uses of the mixture and uses advised against

Identified use: Tyre bead lubricant.

For industrial use only

# 1.3. Details of the supplier of the safety data sheet

Supplier Auto4, Unit 4a, Park Lane Business Court, Park Lane, Kirkby-

in-Ashfield, Nottingham, Nottinghamshire, NG17 9GU

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification:



## 2.2. Label elements

Labelling: Not classified as hazardous for supply

#### 2.3. Other hazards

See Section 4

# **SECTION 3: Composition/information on ingredients**

Ruglyde Tyre Bead Lube Page 1 of 7

#### 3.2. Mixtures

Ingredient	Composition	CAS No	EC No	Risk/Hazard Phrases
Water	>60			
Cellosize Hydroxyethyl	<1%	Mixture		R11 R36 R67
Cellulose				H225 H319 H336
Polyethylene Glycol	<1%	25322-68-3	500-038-2	
Ethoxylated Fatty Alcohol	<1%	78330-21-9		R22 R41 H302 H318
Calgon	<1%	68915-31-1	272-808-3	
Green Dye	<1%	N/A		

See Section 16 for the full text of Risk/Hazard Phrases.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Skin Contact: Remove all contaminated clothes unless stuck to skin. Wash skin

thoroughly with plenty of water. If symptoms develop, seek

medical attention

Eye Contact: Remove contact lenses. Flush copiously with water for at least

15 minutes holding eyelids apart. If irritation/discomfort occurs,

seek medical attention.

Ingestion: Accidental ingestion is an unlikely event. Wash out mouth with

water and give water to drink if conscious. DO NOT induce vomiting. Seek Medical attention. NEVER GIVEN ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Inhalation: Remove to fresh air and keep at rest. If discomfort occurs or

symptoms develop, seek medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin Contact: Can cause skin irritation

Eye Contact: Irritating to eyes

Ingestion: Accidental ingestion is an unlikely event. Harmful if swallowed

in large doses.

Inhalation: Avoid breathing vapour. High concentrations of mist may give

rise to respiratory irritation. Mist unlikely to occur during

normal use.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

If in any doubt, seek medical attention.

# **SECTION 5: Firefighting measures**

Page 2 of 7

5.1. Extinguishing media

Extinguishing media: The product itself is non-flammable. Use extinguishing

measures appropriate to local circumstances and the surrounding

environment.

5.2. Special hazards arising from the substance or mixture

Exposure Hazards: Avoid breathing vapours.

Forms slippery greasy layers with water.

5.3. Advice for firefighters

Advice for firefighters: Avoid breathing vapours

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Product may cause slip hazard

Avoid contact with skin and eyes. Do not breathe vapour mist.

Use personal protective equipment – see Section 8

**6.2.** Environmental precautions

Environmental precautions: DO NOT allow to enter drains and watercourses.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Dispose of as Waste in accordance with Local and National

Regulations. Soak up with inert absorbent material, sweep up or

shovel into suitable containers for disposal.

#### 6.4. Reference to other sections

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Handling requirements:

EYES: Avoid prolonged/repeated contact. Wear goggles/visor if

splashing is possible.

SKIN: Wear gloves in accordance with BS EN374 during prolonged

use.

INHALATION: Wear respiratory protection if confined/poorly ventilated.

OTHER: Keep away from food and drink. Wash hands before breaks and

at end of work day.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, dry, well-ventilated area. Avoid direct sunlight

and freezing temperatures.

Suitable packaging: Store in tightly closed original containers.

Ruglyde Tyre Bead Lube Page **3** of **7** 

Other data:

7.3. Specific end use(s)

Specific use: The specific uses for this product are detailed in section 1.2.

## **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

Workplace exposure limits: No information is applicable to this product.

**8.2. Exposure controls** 

PROTECTIVE GOGGLES

GLOVES IN ACCORDANCE WITH BS EN374

PROTECTIVE CLOTHING

Engineering measures: Ensure good ventilation in the workplace area

Respiratory protection: Wear respiratory protection if workplace is confined or poorly

ventilated

Hand protection: Gloves in accordance with BS EN374

Eye protection: Goggles

Skin protection: Gloves in accordance with BS EN374, protective clothing Other protection: General safety and hygiene measures. Do not get in eyes, on

skin, or on clothing. Wash hands thoroughly after handling. Use only outdoors or in well ventilated areas. Do not eat, smoke or

drink when using this product.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance: Liquid
Colour: Green
Odour: Turbid
Solubility in water: Soluble

9.2. Other information

pH value:

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Ruglyde Tyre Bead Lube Page 4 of 7

Reactivity: No known reaction with any other product.

10.2. Chemical stability

Chemical stability: Stable under normal temperature conditions and recommended

10.3. Possibility of hazardous reactions

Hazardous reactions: No hazardous reactions if stored and handled as indicated

10.4. Conditions to avoid

Conditions to avoid: Freezing temperatures

10.5. Incompatible materials

Materials to avoid:

10.6. Hazardous decomposition products

Haz. decomp. products:

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Toxicity values:

Symptoms/routes of exposure

Skin contact: Can cause skin irritation

Eye contact: Irritating to eyes

Ingestion: Harmful if swallowed in large doses

Inhalation: Avoid breathing vapour mist. High concentrations of mist may

give rise to respiratory irritation

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Eco toxicity values: The product components are not classified as environmentally

> hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

the environment

12.2. Persistence and degradability

No data available Persistence and degradability:

12.3. Bioaccumulative potential

Page 5 of 7

Bioaccumulation: No data available

12.4. Mobility in soil

No data available Mobility:

12.5. Results of PBT and vPvB assessment

Results: No data available

12.6. Other adverse effects

Additional information: No data available

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Disposal operations: Constitutes a special waste. Licensed waste contractor to

dispose of any waste.

Disposal of packaging: Empty packaging can be disposed of in accordance with the

2005 Hazardous Waste Regulations and amendments.

## **SECTION 14: Transport information**

**14.1. UN number** 

14.2. UN proper shipping name

14.3. Transport hazard class(es) Not classified as dangerous goods for transport.

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This product is not classified as harmful in use under the CHIP Regulations. The information below is given as good handling advice.

15.2. Chemical safety assessment

## **SECTION 16: Other information**

**General Information:** 

Ruglyde Tyre Bead Lube Page 6 of 7

This Safety Data Sheet is in accordance with Commission Regulation (EU) No 453/2010. Only trained personnel should use this material.

#### **Risk Statement in Full**

KH	Highly flammable
R22	Harmful if swallowed
R34	Causes burns
R36	Irritating to eyes
R37	Irritating to respiratory system
R41	Risk of serious damage to eyes
R67	Vapours may cause drowsiness or dizziness

#### **Hazard Statements in Full**

H225	Highly flammable liquid and vapour
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

#### Notes for Risk Phrases and Hazard Statements in Full

The full text for Risk Phrases and Hazard Statements in section 16 relates to the reference numbers in sections 2 and 3 and not necessarily the finished product classification.

#### Legal Disclaimer:

The information provided in this Safety Data Sheet is believed to be correct but does not purport to be all inclusive and does not constitute the users' own assessment of the workplace risk as required by other health and safety legislation. The application, use and processing of related products are beyond our control and therefore entirely your own responsibility. The company shall not be held liable for any damage resulting from handling or from contact with the above produce.

This product should not be used for purposes other than those for which it is designed. The information contained in this safety data sheet is based on present knowledge and current national legislation and meets the requirements of the Chemicals (Hazard Information and Packaging) Regulations. It provides guidance on health, safety and environmental aspects of the product and should not be construed as a guarantee of technical performance or suitability for particular applications.

Ruglyde Tyre Bead Lube Page 7 of 7