

Auto 4 Ltd. Unit 4a, Park Court, Park Lane Business Park, Kirkby-in-Ashfield, Nottinghamshire. NG17 9GU General Tel: 01623 727360 Fax: 01623 721950 Email: sales@auto4.co.uk Web: www.auto4.co.uk

Marvel Air Tool Oil

DISTRIBUTOR

MATERIAL SAFETY DATA SHEET page 1 of 3

PRODUCT NAME: Marvel oil

CHEMICAL NAME: Fuel and oil additive

NFPA CODE: CAS No: N/A-mixture

HAZARDOUS INGREDIENTS

Solvents-mineral spirits-30%-CAS # 64742-88-7 Naphthenic base oil distillate-67%-CAS # 64742-34-3 OSHA-ACGIH-see health hazard data

PHYSICAL DATA

Vapour pressure: 2mm Hg @ 68

Specific gravity: 9

Water solubility: negligible

Percent volatile:

Vapour density:

Evaporation rate:

not determined
not determined

Odour: mild

Appearance: red colour liquid

FIRE AND EXPLOSION DATA

Flash point: 140 F

Upper flammable limit: not determined Lower flammable limit: not determined

Extinguishing media: CO2, dry chemical, foam, water spray, water fog **Unusual fire and explosion hazards:** do not store or mix with strong oxidants

HEALTH HAZARD DATA

Eye irritation: mild

Skin irritation: mild irritation may occur with prolonged or

Repeated contact. Testing of similar oils has produced skin tumours in experimental animals after prolonged and repeated contact.

MARVEL OIL (CONTINUED) page 2 of 3

EMERGENCY FIRST AID PROCEDURES

Eye: flush with water until irritation subsides.

Skin: wash with soap and water

Oral: do not induce vomiting; give milk or water

to dilute stomach contents.

STABILITY

Stability: stable

Incompatibility: oxidising agents **Polymerisation:** will not occur

SPILL OR LEAK PROCEDURES

Spill procedures: recover free liquid, add absorbent to spill area **Waste disposal:** keep product out of sewers and watercourses

disposal should be in accordance with local and

national laws

SPECIAL PROTECTION

Ventilation: mechanical ventilation as needed

Gloves: use chemical resistant gloves as needed to

prevent prolonged or repeated skin contact

Eye contact: product minimally irritating to eyes, use safety

glasses when eye contact may occur

Other: use chemical resistant apron or other impervious

clothing if needed to avoid prolonged or repeated

skin contact

SPECIAL PRECAUTIONS

Keep away from heat and open flame, contains refined petroleum distillates, if swallowed do not induce vomiting, if ingested call physician immediately

MARVEL OIL (CONTINUED) page 3 of 3

TRANSPORTATION INFORMATION

DOT shipping name: petroleum lube oil **DOT hazard class:** combustible liquid

DOT ID number: NA1270 **NMFC ID number:** 155250

All information, recommendations, and suggestions appearing herein concerning this product are based upon data obtained from the manufacturer and/or recognised technical sources; however, Marvel Oil Company INC. makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of the product. Since actual use by others is beyond our control, no warranty, expressed or implied is made by marvel as to the effects of such use, the results to be obtained or the safety or toxicity of this product, nor does marvel assume any liability arising out of the use by others of the product referred to herein. The data in this MSDS relate to the specific material designated herein and do not relate to use in combination with any other material or process.

DATE OF ISSUE 01/2001