

Auto 4 Ltd. Unit 4a, Park Court, Park Lane Business Park, Kirkby-in-Ashfield, Nottinghamshire. NG17 9GU General Tel: 01623 727360

Fax: 01623 721950 Email: sales@auto4.co.uk Web: www.auto4.co.uk

SAFETY DATA SHEET 202100 WHEEL DEGREASER

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name WHEEL DEGREASER

Company Auto4, Unit 4a, Park Lane Business Court, Park Lane, Kirkby-in-Ashfield, Nottingham,

Nottinghamshire, NG17 9GU.

sales@auto4.co.uk
www.auto4.co.uk

Telephone 01623 727360 (Kirkby) / 01235 854027 (Didcot)

Fax 01623 721950

Product code 202100

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Special Boiling Point Spirit 100/140	30 - 40%	64742-49-0	265-151-9	F;R11 Xi;R38 N;R51/53 Xn;R65
Acetone	I - I0%	67-64-I	200-662-2	F; R11 Xi; R36 R66 R67
Isopropanol (Propan-2-ol)	10 - 20%	67-63-0	200-661-7	F; R11 Xi; R36 R67
Low boiling point naphtha - solvent naphtha (petroleum), light aliph.2	30 - 40%	64742-89-8	265-192-2	F;R11 Xi;R38 N;R51/53 Xn;R65 R67

3. HAZARDS IDENTIFICATION

Main hazards

Repeated exposure may cause skin dryness or cracking. Highly flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated

clothing. Seek medical attention if irritation or symptoms persist.

Eye contact Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open.

Seek medical attention if irritation or symptoms persist.

Inhalation Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation

of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

DO NOT INDUCE VOMITING.

WHEEL DEGREASER

Revision 0

Revision date

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon dioxide (CO2)

Fire hazards Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel

considerable distance to source of ignition and flash back.

Protective equipment Self-contained breathing apparatus. Wear protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all

sources of ignition. Evacuate personnel to a safe area.

Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for

disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion

proof equipment. Keep away from sources of ignition - No smoking.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled

containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Acetone WEL 8-hr limit ppm: 500 WEL 8-hr limit mg/m3: 1210

WEL 15 min limit ppm: 1500 WEL 15 min limit mg/m3: 3620

 Isopropanol
 WEL 8-hr limit ppm: 400
 WEL 8-hr limit mg/m3: 999

 (Propan-2-ol)
 WEL 15 min limit ppm: 500
 WEL 15 min limit mg/m3: 1250

Engineering measures Ensure adequate ventilation of the working area.

Respiratory protection Wear suitable respiratory equipment when necessary.

Hand protection Chemical resistant gloves (PVC)

Eye protection Approved safety goggles.

Protective equipment Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid.

ColourColourless.OdourStrong.Boiling point104-121°C

10. STABILITY AND REACTIVITY

Flash point

Stability Stable under normal conditions.

1°C

Conditions to avoid Heat, sparks and open flames.

Materials to avoid Oxidising agents.

WHEEL DEGREASER

Revision 0

Revision date

11. TOXICOLOGICAL INFORMATION

Toxicological information

Special Boiling Point Spirit 100/140 Oral Rat LD50 = >2000mg/kg

Isopropanol Oral Rat LD50 = 4700-5500mg/kg

Dermal Rabbit LD50 = >12800mg/kg Inhalation Rat LC50/4 h = 47-73mg/l

12. ECOLOGICAL INFORMATION

EcotoxicityToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Isopropanol Daphnia EC50/48h = 4600mg/l mg/l

Fathead minnows LC50/96h = 9600mg/l

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

Further information The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

Safety phrases

Labelling The product is classified in accordance with 67/548/EEC. R65 - Harmful: may cause lung damage if

swallowed.

Symbols F - Highly flammable; Xn - Harmful; N - Dangerous for the environment







Risk phrases R66 - Repeated exposure may cause skin dryness or cracking.

RII - Highly flammable.

R36/38 - Irritating to eyes and skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

R67 - Vapours may cause drowsiness and dizziness.

S9 - Keep container in a well-ventilated place.

S24 - Avoid contact with skin.

S37 - Wear suitable gloves.

S51 - Use only in well-ventilated areas.

S57 - Use appropriate container to avoid environmental contamination.

S60 - This material and its container must be disposed of as hazardous waste.

 ${\sf S61}$ - ${\sf Avoid}$ release to the environment. Refer to special instructions/safety data sheets.

\$16 - Keep away from sources of ignition - No smoking.

S29 - Do not empty into drains.

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

WHEEL DEGREASER

Revision 0

Revision date

16. OTHER INFORMATION

Text of risk phrases in Section 2

RII - Highly flammable.

R36 - Irritating to eyes.

R38 - Irritating to skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

R67 - Vapours may cause drowsiness and dizziness.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal responsibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.